



## OW LED



OW LED is a series of adjustable LED spotlights, designed for accent, indoor lighting.

**Materials:** Body made of powder painted aluminum in white color, chrome version also available, two axis adjustable LED, two light distributions available, with a focused beam 20° and diffused beam 40°.

**Installation:** Into suspended ceilings.

**Power:** 230 V

### ELECTRICAL DATA

|                         |       |
|-------------------------|-------|
| Light source            | LED   |
| Number of light sources | 1     |
| Light source power      | 4W    |
| Type of equipment       | AC    |
| Voltage rating          | 230 V |
| Light source included   | Yes   |
| Luminaire power         | 4 W   |

### MECHANICAL DATA

|                      |                     |
|----------------------|---------------------|
| Type of installation | For 600x600 ceiling |
| Housing material     | Aluminum            |

### AVAILABLE VARIANTS



| Product code | Light source power [W] | Colour temperature [K] | Beam angle [°] | Colour | Weight [kg] |
|--------------|------------------------|------------------------|----------------|--------|-------------|
| PX0864301    | 1x4                    | 2900                   | 20             | White  | 0.80        |
| PX0864308    | 1x4                    | 5400                   | 20             | White  | 0.80        |
| PX0864315    | 1x4                    | 2900                   | 40             | White  | 0.80        |
| PX0864322    | 1x4                    | 5400                   | 40             | White  | 0.80        |
| PX0864401    | 1x4                    | 2900                   | 20             | Chrome | 0.32        |
| PX0864408    | 1x4                    | 5400                   | 20             | Chrome | 0.32        |
| PX0864415    | 1x4                    | 2900                   | 40             | Chrome | 0.32        |
| PX0864422    | 1x4                    | 5400                   | 40             | Chrome | 0.32        |

### CERTIFICATES

|                           |      |
|---------------------------|------|
| Degree of protection (IP) | IP20 |
| Class of protection       | I    |
| Energy class              | A    |
| CE                        | Yes  |

### LIGHT DATA

|                    |    |
|--------------------|----|
| Light distribution | DI |
|--------------------|----|



## DIMENSIONS

| Product code | H [mm] | F [mm] |
|--------------|--------|--------|
| PX0864301    | 100    | 118    |
| PX0864308    | 100    | 118    |
| PX0864315    | 100    | 118    |
| PX0864322    | 100    | 118    |
| PX0864401    | 75     | 103    |
| PX0864408    | 75     | 103    |
| PX0864415    | 75     | 103    |
| PX0864422    | 75     | 103    |

H = Height / Depth | F = Outer diameter

## MOUNTING HOLES

| Product code | A [mm] | B [mm] |
|--------------|--------|--------|
| PX0864301    | 109    | 109    |
| PX0864308    | 109    | 109    |
| PX0864315    | 109    | 109    |
| PX0864322    | 109    | 109    |
| PX0864401    | 95     | 95     |
| PX0864408    | 95     | 95     |
| PX0864415    | 95     | 95     |
| PX0864422    | 95     | 95     |

A = Spacing length | B = Spacing width